

A blue portable ultrasonic welding unit with a black hose and a red welding tip. The unit has a handle and a label on the front. The hose is coiled around the unit, and the red tip is at the end of the hose.



TYPE		VD 25	VD 35
Needle Ø -Flaschen-Ø Ø aiguiille - Ø ago	mm	25	35
Needle length -Flaschenlänge Longueur aiguille - Lunghezza ago	mm	290	270
Vibrations -Schwingungen Vibrations - N° vibrazioni	Vpm	12000	12000
Amplitude -Schwingweite Amplitude - Ampiezza	mm	0.65	1.3
Compacting power -Verdichtungsleistung Pouvoir de compacité - Capacità di compattare	m³/h	6.25	9
Action Ø -Wirkungs Ø Ø action - Ø azione	mm	650	850
Centrifugal force -Zentrifugalkraft Force centrifuge - Forza centrifuga	Kg KN	80 0.8	170 1.7
Needle weight -Flaschengewicht Poids aiguille - Peso ago	Kg	0.8	1.5
Shaft length -Biegewellenlänge Longueur transmission - Lunghezza trasmissione	m	2-3-4	2-3-4
Shaft weight -Biegewellengewicht Poids transmission - Peso trasmissione	Kg	2.5 ÷ 7	2.5 ÷ 7

SINGLE PHASE -EINPHASIG MONOPHASE - MONOFASE	M2300D
Input tension -Versorgungsspannung u. Antrieb Tension d'alimentation - Tensione alimentazione	220 - 230 V 50 - 60 Hz
Power - Leistung Puissance - Potenza	3 HP (PS) 2300 W
RPM -U/min TPM - Giri al minuto	18000
Protection -Schutzart Protection - Protezione	IP 54
Total weight -Gesamtgewicht Poids total - Peso totale	6 Kg

N.B.: Rights reserved to modify technical specifications.

N.B.: Angaben ohne Gewähr. Änderungen können ohne Vorankündigung vorgenommen werden.

N.B.: Toutes données portées dans le présent catalogue n'engagent pas le fabricant. Elles peuvent être modifiées à tout moment.

N.B.: Tutti i dati riportati nel presente catalogo non sono impegnativi e possono subire variazioni in qualsiasi momento.